

## Type Approval Certificate Extension

This is to certify that Certificate No. 04/00046 for the undernoted products is extended and renumbered as shown.

This certificate is issued to:

**PRODUCER** 

Wolf Safety Lamp Company Ltd

PLACE OF

Saxon Road Works Sheffield, S80YA

**PRODUCTION** 

United Kingdom (UK)

DESCRIPTION

Compressed Air Powered Lamp

**TYPE** 

Wolf ATEX Turbolite Range

A-TL44A -Baylight (Aluminium Construction)

A-TL44B -Baylight (Brass Construction)

A-TL45A -Floodlight (Aluminium Construction)

A-TL45B -

Floodlight (Brass Construction)

APPLICATION

Group II surface applications in the marine and offshore industries, as Category 2 equipment, for zone 1 & 2 potentially explosive gases,

vapours, mists and dust, where T4 temperature class permits

**STANDARDS** 

EN 50014: 1997

EN 50018: 2000 EN 50019: 2000 EN 1127-1: 1997

EN 13463-1: 2001 EN 50281-1-1: 1998

**RATINGS** 

Code:

Ambient Temp.:

-20° C to +55° C IP 66 (when running)

**Enclosure: Enclosure:** 

IP 40 (when not running)

Certificate No.

04/00046(E1)

**Issue Date** 

22 October 2009

**Expiry Date** 

15 June 2014

Sheet

1 of 2

R.M. Kelkar

London Design Support Services Lloyd's Register EMEA

Lloyd's Register EMEA 71 Fenchurch Street, London EC3M 4BS

Lloyd's Register, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as the 'Lloyd's Register Group'. The Lloyd's Register Group assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register Group entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.



RATINGS (continued)

Compressed air driving integral

turbine generator (pressure):

5 to 8 bar

Lamp:

24 V 250 W (halogen)

## OTHER CONDITIONS

- The equipment shall only be supplied with air from a clean, dry source that is free from contamination with hazardous gas, dust or fibres.
- 2. When the equipment is used in the presence of combustible dust, the air outlet shall be fitted with additional hose so that it is piped to a safe area instead of venting into the hazardous area.
- 3. The hoses that are fitted to this equipment shall be anti-static with a resistance between 10<sup>4</sup> and 10<sup>8</sup> ohms.
- 4. Air supply should be shut off for at least two minutes before dismantling.

"This Certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register EMEA of any modification or changes to the equipment in order to obtain a valid certificate."

The attached Design Appraisal Document No. 04/00046(E1) and its supplementary Type Approval Terms and Conditions form part of this Certificate.

All other details remain as the previous Certificate No. 04/00046 to which this extension should be attached.

Certificate No.

04/00046(E1)

Issue Date

22 October 2009

**Expiry Date** 

15 June 2014

Sheet

2 of 2

R.M. Kelkar

London Design Support Services Lloyd's Register EMEA

Lloyd's Register EMEA 71 Fenchurch Street, London EC3M 4BS

Lloyd's Register, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as the 'Lloyd's Register Group'. The Lloyd's Register Group assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register Group entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Part 1B
Subject: Electrical Equipment (Not Environmentally Tested)
Product: Safety Apparatus (Part 1B)

	Description of Product				
Producer/Licence No.	Туре	Details of Approval	Application	Remarks	Cert. No.
Ltd, Pov. Saxon Road Works, (AT Sheffield, S8 0YA, United Kingdom (UK).	ATEX Turbolite ange)	Code: Ex II 2 GD II T4 (Ta = 55°) T135°C  Ambient Temp.: -20° C to +55° C  Enclosure: IP 66 (when running)  Enclosure: IP 40 (when not running)  Compressed air driving integral turbine generator (pressure): 5 to 8 bar  Lamp: 24 V 250 W (halogen)	Group II surface applications in the marine and offshore industries, as Category 2 equipment, for zone 1 & 2 potentially explosive gases, vapours, mists and dust, where T4 temperature class permits.	Expires: 15 June 2014  EN 50014: 1997 EN 50018: 2000 EN 50019: 2000 EN 1127-1: 1997 EN 13463-1: 2001 EN 50281-1-1: 1998  Refer to Certificate for applicable	04/00046(E1)